

Laykold® Line Paint

1C acrylic line marking paint

This is a water-based and solvent-free acrylic emulsion. Its main area of application is the marking of lines on Laykold coatings.

Product specifications

Viscosity	@ 23 °C; 50 % humidity	30,000 ± 5,000 mPas
Processing temperature		10 °C – 54 °C
Setting		2–4 hours

Processing specifications

The previously applied acrylate coating should be left to cure for at least 24 hours before applying Laykold Line Paint. Laykold Line Paint must be mixed thoroughly prior to use. Do not add any water at all. We recommend applying it with a high-quality paint roller.

Safety warnings

Smoking and naked lights are strictly prohibited while working with the product. Enclosed spaces should be adequately ventilated while working with the product. In addition, we recommend wearing protective goggles and gloves. In the event of contact with the skin or eyes, wash the affected areas thoroughly with soap and water.

If symptoms persist, seek medical attention.

Packaging

5 kg bucket

Storage

Laykold Line Paint should be stored in a cool and dry location. Provided that it is kept under the specified conditions inside unopened original containers, it has a storage life of 6 months. If Laykold Line Paint is stored for longer than this, you must check that the product is still fit for use before using it. Once opened, buckets should be carefully resealed and protected against moisture. The remaining contents should be used up swiftly.