

Laykold® Masters Bond Kote

1C latex primer

This is a single-component, latex emulsion adhesive primer. It is mainly used for bonding glass fibre fabric to prefabricated rubber mats.

Product specifications

Density	@ 23 °C; 50 % humidity	1.02 ± 0.05 g/cm ³
Viscosity	@ 20 °C	4,000 ± 500 mPas
Tensile strength	@ 23 °C; 50 % humidity	3.66 N/mm ²
Elongation	@ 23 °C; 50 % humidity	498.3 %
Setting		2–4 hours
Processing temperature		10 °C – 54 °C

Processing specifications

Prior to application, make sure that the existing surface is undamaged, dry and free from oils and other adhesion inhibitors. Any flaking and peeling, holes and other forms of damage must be repaired. Please also observe the sub-floor properties and condition recommended for Laykold systems.

Safety warnings

Smoking and naked lights are strictly prohibited while working with the product. Enclosed spaces should be adequately ventilated while working with the product. In addition, we recommend wearing protective goggles and gloves. In the event of contact with the skin or eyes, wash the affected areas thoroughly with soap and water.

If symptoms persist, seek medical attention.

Packaging

16 kg bucket

Storage

Laykold Masters Bond Kote should be stored in a cool and dry location. Provided that it is kept under the specified conditions inside unopened original containers, it has a storage life of 6 months. If Laykold Masters Bond Kote is stored for longer than this, you must check that the product is still fit for use before using it. Once opened, buckets should be carefully resealed and protected against moisture. The remaining contents should be used up swiftly.