

## Laykold® Masters Filler

### 1C acrylic latex emulsion

This is a prefilled, single-component acrylic latex emulsion. Laykold Masters Filler can be used as a filler layer before applying a Laykold Masters Topcoat. Laykold Masters Filler contains no asbestos, lead or mercury.

#### Product specifications

<b>Viscosity</b>	@ 23 °C; 50 % humidity	25,000 ± 5,000 mPas
<b>Mixing ratio</b>	Laykold Masters Filler : Water	5 : 1
<b>Processing temperature</b>		10 °C – 54 °C
<b>Setting</b>		2–4 hours

#### Processing specifications

Prior to application, make sure that the existing surface is undamaged, dry and free from oils and other adhesion inhibitors. Any flaking and peeling, holes and other forms of substrate damage must be repaired. Similarly, all unevenness must be levelled out before starting the surface treatment. Please also observe the sub-floor properties and condition recommended for Laykold systems.

When water is added, the materials must be mixed together to create a homogeneous mixture. The product must be applied using a soft rubber squeegee.

#### Safety warnings

Smoking and naked lights are strictly prohibited while working with the product. Enclosed spaces should be adequately ventilated while working with the product. In addition, we recommend wearing protective goggles and gloves. In the event of contact with the skin or eyes, wash the affected areas thoroughly with soap and water.

If symptoms persist, seek medical attention.

#### Packaging

25 kg bucket

#### Storage

Laykold Masters Filler should be stored in a cool and dry location. Provided that it is kept under the specified conditions inside unopened original containers, it has a storage life of 6 months. If Laykold Masters Filler is stored for longer than this, you must check that the product is still fit for use before using it. Once opened, buckets should be carefully resealed and protected against moisture. The remaining contents should be used up swiftly.