

melos

Laykold[®] GUIDE

Customer Version



FOR TENNIS AND
MULTISPORTS FACILITIES
**ACRYLIC SPORTS
SURFACES**

TENNIS
BASKETBALL
VOLLEYBALL
FOOTBALL

OVER 100,000,000 m² OF LAYKOLD
SPORTS SURFACES INSTALLED SINCE 1970!

Laykold designed FOR ALL SPORTS



The Laykold acrylic system is an all-weather hard court coating that is both hard-wearing and durable. It can be easily adapted to meet a whole host of criteria in the areas of performance, playability and appearance. For instance, a specially made rubber cushion can be integrated into the system to improve the cushioning effect and, in turn, the comfort of play. The wide choice of colors allows you to add a creative splash to your asphalt or concrete surfaces whether old or new.

Thanks to the minimal maintenance requirements and low installation costs, you can reinvigorate existing concrete and asphalt surfaces, and extend the life of existing courts. The main application areas are tennis courts and multi-sports surfaces (for basketball, volleyball, football). Laykold is also a popular solution for roller sports or schools.


Laykold was first used in the 1920s until 1930s. Since then, this surface has been installed at more than 100,000 sports facilities throughout the world. During the tennis boom of the 1960s and 70s, Laykold became established as one of the few materials suitable for hard court surfaces. Thanks to the versatility that it offers today, Laykold has become the global market leader for outdoor tennis courts.

THE RIGHT SYSTEM TO SUIT ANY REQUIREMENTS

	HARD COURT SYSTEMS	LAYKOLD COLORCOAT	LAYKOLD ADVANTAGE	LAYKOLD MASTERS COLOR	CUSHIONED SYSTEMS	LAYKOLD MASTERS 5 LAYKOLD MASTERS 5 GT	LAYKOLD MASTERS 8	LAYKOLD MASTERS GEL
UV-resistant colors		■	■	■		■	■	■
Slip-resistant		■	■	■		■	■	■
Durable, recoatable		■	■	■		■	■	■
Glare-free		■	■	■		■	■	■
Wide choice of colors		■	■	■		■	■	■
Water-impermeable		■	■	■		■	■	■
Resource conservation		■	■	■		■	■	■
Factory-textured Topcoat			■	■		■	■	
High abrasion resistance				■		■	■	■
Cushioning						■	■	■
Developed for existing sub-floors with imperfections in the form of						■	■	■




CONTENT	
References	4–11
Color chart	10
Laykold ColorCoat	12
Laykold Advantage	13
Laykold Masters Color	14
Laykold Masters 5 / Masters 5 GT	15
Laykold Masters 8	16
Laykold Masters Gel	17
Dimensions	18–19
Sub-floor recommendation	20
Installation of Laykold Systems	21
Recommended care and cleaning	22–23



**Nike Stanton Street
Courts by KAWS**

**Andrew Jackson
Elementary School,
Santa Ana CA
Soccer Court**



Fed Cup Asheville

© Steve Atkins, Fox Cove Photography



**Club Mediterra
Pickleball Courts**



**Seed School,
Washington DC
Soccer Court**





Hard Rock Stadium
Miami, Florida



MAKE YOUR **LAYKOLD** COURT UNIQUE!

Laykold tennis courts can now be individually designed with a logo and a selection of 17 standard colors. Fresh colors provide a unique playing feel and an integrated logo, e.g. from the club - makes the Laykold Court individual and unique.

[Anything is possible – create it now!](#)







Color chart

Standard colors

	Beach beige approx. RAL 1011		Pumpkin approx. RAL 2000		Candy red approx. RAL 3002
	Burgundy approx. RAL 3005		Red approx. RAL 3009		Coral approx. RAL 3017
	Purple approx. RAL 4005		Royal Purple approx. RAL 4007		Dark blue approx. RAL 5011
	Light blue approx. RAL 5015		Grass green approx. RAL 6017		Spring green approx. RAL 6018
	Dark green approx. RAL 6020		Dark grey approx. RAL 7022		Light grey approx. RAL 7036
	Arctic blue This color does not correspond to any RAL color.		Teal This color does not correspond to any RAL color.		

Tournament colors

	US Open Blue		Miami Open Biscayne Blue
	US Open Green		Miami Open Oasis Blue



More colors on request.

¹ The RAL color specifications are non-binding approximations. Deviations in color reproduction in the illustrations are due to printing technology. We recommend ordering color charts.



Laykold® ColorCoat


Cost-effective, acrylic hard court coating system

The Laykold ColorCoat acrylic system is an all-weather hard court coating that is both hard-wearing and durable. Its main areas of application are tennis courts and multi-sports surfaces (for basketball, volleyball, football). The wide choice of colors allows you to add a creative splash to your asphalt or concrete surfaces whether old or new.

Laykold ColorCoat is laid seamlessly without any joints. With its textured and water-impermeable surface, it offers optimum sporting characteristics.

-  WIDE CHOICE OF COLORS
-  UV-RESISTANT COLORS
-  SLIP-RESISTANT
-  DURABLE
-  WATER-IMPERMEABLE
-  RESOURCE CONSERVATION
-  CERTIFIABLE

System structure



System properties

PROPERTIES	STANDARD	RESULT
Thickness	DIN EN 1969	≥ 1 mm
Friction	DIN EN 13036-4	101 (dry) / 60 (wet)
Abrasion resistance	DIN EN ISO 5470-1	1.02 g
ITF coefficient of restitution	ITF CS 01 / 02	0.79
ITF coefficient of friction	ITF CS 01 / 02	0.68
ITF Court Pace Rating	ITF CS 01 / 02	35 (medium)



Laykold® Advantage


Durable multi-sports surfaces with Laykold Advantage

The Laykold Advantage acrylic system is an all-weather hard court coating that is both hard-wearing and durable. Its main areas of application are tennis courts and multi-sports surfaces (for basketball, volleyball, football). Regardless of how and where it is installed, a consistent surface structure can be achieved thanks to the defined quartz sand prefilling. Laykold Advantage is available in several colors, allowing you to add a creative splash to your asphalt or concrete surfaces whether old or new.

Laykold Advantage is laid seamlessly without any joints. With its textured and water-impermeable surface, it offers optimum sporting characteristics.

-  WIDE CHOICE OF COLORS
-  UV-RESISTANT COLORS
-  SLIP-RESISTANT
-  DURABLE
-  WATER-IMPERMEABLE
-  FACTORY-TEXTURED TOPCOAT
-  RESOURCE CONSERVATION
-  CERTIFIABLE

System structure



System properties

PROPERTIES	STANDARD	RESULT
Thickness	DIN EN 1969	≥ 1 mm
Friction	DIN EN 13036-4	101 (dry) / 60 (wet)
Abrasion resistance	DIN EN ISO 5470-1	1.02 g
ITF coefficient of restitution	ITF CS 01 / 02	0.79
ITF coefficient of friction	ITF CS 01 / 02	0.68
ITF Court Pace Rating	ITF CS 01 / 02	35 (medium)



Laykold® Masters Color


High abrasion resistance with Laykold Masters Color

The Laykold Masters Color acrylic system is an all-weather hard court coating that is both hard-wearing and durable. Its main areas of application are tennis courts and multi-sports surfaces (for basketball, volleyball, etc.). One of the stand-out features of Laykold Masters Color is its high abrasion resistance. Regardless of how and where it is installed, a consistent surface structure can be achieved thanks to the defined quartz sand prefilling. Laykold Master Color is available in several colors, allowing you to add a creative splash to your asphalt or concrete surfaces whether old or new.

Laykold Masters Color is laid seamlessly without any joints. With its textured and water-impermeable surface, it offers optimum sporting characteristics.

- WIDE CHOICE OF COLORS
- UV-RESISTANT COLORS
- SLIP-RESISTANT
- DURABLE
- LOW ABRASION
- WATER-IMPERMEABLE
- FACTORY-TEXTURED TOPCOAT
- RESOURCE CONSERVATION
- CERTIFIABLE

System structure



System properties

PROPERTIES	STANDARD	RESULT
Thickness	DIN EN 1969	≥ 1 mm
Friction	DIN EN 13036-4	99 (dry) / 60 (wet)
Abrasion resistance	DIN EN ISO 5470-1	0.50 g
ITF coefficient of restitution	ITF CS 01 / 02	0.79
ITF coefficient of friction	ITF CS 01 / 02	0.68
ITF Court Pace Rating	ITF CS 01 / 02	35 (medium)



Laykold® Masters 5


Comfort of play like no other thanks to the cushioning effect of the Laykold Masters 5

Laykold Masters 5 is an all-weather acrylic system that is both hard-wearing and durable with a cushioning effect to improve the comfort of play. Its main areas of application are tennis courts and multi-sports surfaces (for basketball, volleyball, football). Regardless of how and where it is installed, a consistent surface structure can be achieved thanks to the defined quartz sand prefilling. Laykold Masters 5 is available in several colors, allowing you to add a creative splash to your asphalt or concrete surfaces whether old or new.

Laykold Masters 5 is laid seamlessly without any joints. With its textured and water-impermeable surface, it offers optimum sporting characteristics.

- WIDE CHOICE OF COLORS
- UV-RESISTANT COLORS
- SLIP-RESISTANT
- DURABLE
- LOW ABRASION
- GOOD CUSHIONING EFFECT
- WATER-IMPERMEABLE
- FACTORY-TEXTURED TOPCOAT
- RESOURCE CONSERVATION
- CERTIFIABLE

System structure



System properties

PROPERTIES	STANDARD	RESULT
Thickness	DIN EN 1969	5 mm
Impact absorption	DIN EN 14808	14 %
Vertical deformation	DIN EN 14809	0.5 mm
Vertical ball behaviour	DIN EN 12235	98 %
Angled ball behaviour	DIN EN 13865	29 (slow)
Friction	DIN EN 13036-4	99 (dry) / 65 (wet)
Abrasion resistance	DIN EN ISO 5470-1	0.52 g
Tensile strength (EN 12230)	DIN EN 12230	0.65 MPa / 60 %




Also available as
Laykold® Masters 5 GT
The new sustainable elastic mat – contains recycled tennis balls.

Laykold® Masters 8

Optimum sporting characteristics with Laykold Masters 8

Laykold Masters 8 is an all-weather acrylic system that is both hard-wearing and durable and features a superb cushioning effect to improve the comfort of play. Its main areas of application are tennis courts and multi-sports surfaces (for basketball, volleyball, football). Regardless of how and where it is installed, a consistent surface structure can be achieved thanks to the defined quartz sand prefilling. Laykold Masters 8 is available in several colors, allowing you to add a creative splash to your asphalt or concrete surfaces whether old or new. Laykold Masters 8 is laid seamlessly without any joints. With its textured and water-impermeable surface, it offers optimum sporting characteristics.

System structure



System properties

PROPERTIES	STANDARD	RESULT
Thickness	DIN EN 1969	8 mm
Impact absorption	DIN EN 14808	23 %
Vertical deformation	DIN EN 14809	0.8 mm
Vertical ball behaviour	DIN EN 12235	103 %
Angled ball behaviour	DIN EN 13865	30 (slow)
Friction	DIN EN 13036-4	99 (dry) / 65 (wet)
Abrasion resistance	DIN EN ISO 5470-1	0.52 g
Tensile strength (EN 12230)	DIN EN 12230	1.81 Mpa / 53 %

- WIDE CHOICE OF COLORS
- UV-RESISTANT COLORS
- SLIP-RESISTANT
- DURABLE
- LOW ABRASION
- EXCELLENT CUSHIONING EFFECT
- WATER-IMPERMEABLE
- FACTORY-TEXTURED TOPCOAT
- RESOURCE CONSERVATION
- CERTIFIABLE




Laykold® Masters Gel

The cushion court system of renewable resources

Laykold® Masters Gel is a revolutionary cushion court system made from more than 60 % renewable resources. The all-weather system offers a wide range of benefits for all ages and abilities. From the recreational athlete to the professional, Laykold® Masters Gel provides more than 17 % force reduction and improves player performance by reducing joint impact and body fatigue. Whether you are playing at the net or baseline, you can be sure that both ball speed and stance remain the same.

- EXCELLENT CUSHIONING EFFECT
- SEAMLESS
- WIDE CHOICE OF COLORS
- UV-RESISTANT COLORS
- SLIP-RESISTANT
- DURABLE
- LOW ABRASION
- RESOURCE CONSERVATION
- CERTIFIABLE



Recommended care and cleaning

1. General cleaning and maintenance

Laykold systems generally require minimal care and maintenance. The amount of work required depends heavily on the local environmental conditions and how intensively the court is used. The conditions can be divided into two categories:

a. Low-maintenance environments

Environments with low levels of dirt and minimal dust. This means, for example, that indoor spaces are classed as low-maintenance areas.

a) Outdoor areas

Depending on the amount of surface dirt, the courts must be cleaned roughly once a week with a broom, air blower or wet broom. Foreign matter must be washed away with a water hose if possible.

b) Indoor areas

Depending on how intensively the court is used, indoor areas must be cleaned once every 2 to 4 weeks with a walk-behind (or similar) cleaning machine to get rid of any dust and dirt. Heavy soiling or stains must be removed with a floor scrubber machine with a soft brush/pad. Dirty water should be drained directly from the surface.

b. Maintenance-intensive environments

Environments with significant levels of air pollution (such as dust, foliage and traffic fumes) are classed as high-maintenance environments; generally, these will be outdoor areas.

Use a water hose to remove foreign matter from the surface at least once a week to prevent pollutants from accumulating. If the surface gets dirty or stained, it can be cleaned with a floor scrubber machine with a soft brush/pad. When cleaning the surface, you should also use a biodegradable cleaning agent.

When using a cleaning agent, observe the manufacturer's specifications and rinse it off immediately with clean tap water.

2. Possible types of contamination

a. Contamination caused by vegetation

Courts that have a lot of trees and vegetation nearby must be properly looked after to prevent excessive ingress of organic matter from plants (e.g. leaves and grass clippings). Certain constituents of foliage/plants will cause stains if they are left lying around for too long.

Furthermore, mould may form in these areas if they are allowed to combine with rainwater.

We recommend the following cleaning process:

- Sweep away foreign matter (such as foliage/plants) with a

broom.

- Wash the surface with clean water.
- Use a diluted sodium hypochlorite solution (liquid swimming pool chlorine); the dilution rate will depend on the extent of the mould infestation.
- Spread the solution over the mould-infested area with a broom and leave it to work for 10 to 15 minutes. Do not allow it to dry.
- Hose the surface down thoroughly with clean water to remove any residual solution.
- More heavily infested areas may require additional treatment. In particularly difficult cases, the surface will have to be sprayed with a powerful jet of water and treated with sodium hypochlorite. Other moss and algae killers are available from retail outlets.

b. Contamination caused by organic animal matter

Prolonged exposure to bird droppings and worms will cause the Laykold surface to decompose. Therefore, these contaminants must be removed immediately with a mechanical scraper and/or a high-pressure cleaner. If the desired cleaning results are not achieved, you can use a residue-free, biodegradable cleaning agent (rinse it off with water).

If the organic animal matter cannot be removed, the system may start to blister or flake (with the damage extending as far as the asphalt). In this case, the defect will have to be repaired by a Laykold specialist company.



c. Food and drink residues

We recommend wet cleaning the surface immediately. If any stains appear, use the same cleaning methods as for contamination caused by vegetation.

Treat chewing gum residues with a freeze spray and carefully remove them mechanically with a rubber scraper.

d. Fat and oil residues

We recommend using a residue-free, organic cleaning agent to remove these contaminants. Several cleaning cycles may be required. After treating the area, rinse it with clean water.

e. Signs of wear and tear

Only wear shoes with white and/or abrasion-resistant soles. People using the court should clean their shoes before stepping onto it so that no stones, twigs or other sharp objects can damage the surface. Certain soles may leave black marks on the surface. These marks can generally be removed by using a residue-free, biodegradable cleaning agent and a brush with rigid bristles. Marks caused by shoe soles will be more obvious on new surfaces.

Laykold Masters surfaces are resistant to normal racket contact. Nevertheless, if the surface receives heavy blows from a metal racket at a sharp angle, minor scratches may be caused. This type of damage is normally restricted to the upper layers and can be easily repaired. In this case, the defect should be repaired by a Laykold specialist company.



Notes:

- We recommend that you test all cleaning methods and their effects on an inconspicuous area to make sure they are compatible before you start using them more generally.
- Do not use any solutions made from powdered calcium hypochlorite, as these will leave white residues behind on the surface once dry.
- Keep the product away from plants, animals and children, and wear protective clothing.
- Observe the local environmental regulations.
- Laykold surfaces must not be used on solvent-based products such as thinning agents and similar products.
- Avoid point loads such as metal chair legs, heavy trolleys/carts and stiletto heels.



melos

Melos GmbH
Bismarckstrasse 4 – 10
49324 Melle | Germany
Phone +49 54 22 94 47-0
Fax +49 54 22 59 81
info@melos-gmbh.com
www.melos-gmbh.com