

Features and Benefits

- ✓ Environmentally friendly
- ✓ Water based
- ✓ Contains no solvents or oils
- ✓ Does not contain asbestos, Lead or Mercury
- ✓ Good hiding properties

1.0 General Description

Laykold White Line Paint is a 100% acrylic-based emulsion line marking paint. Formulated without solvents or oils that tend to attack the underlying surface.

Laykold White Line Paint is also environmentally friendly container no asbestos, Lead or Mercury.

Basic Uses: Laykold White Line Paint is used for marking lines over colour coating materials on tennis courts, basketball courts and other recreational surfaces.

2.0 Safety Guidelines

Always wear the recommended personal protective equipment. Avoid contact with eyes, skin, and clothing. Refer to Safety Data Sheet (SDS) for more information.

3.0 Storage and Packaging

Laykold White Line Paint should be kept dry and cool.

Storage temperature should be between 4°C (40°F) and 32°C (90°F).

Packaging: 20 ltr (24kg) (5 gallon) unit



WHITE LINE PAINT

TECHNICAL DATA SHEET

4.0 Coverage

Laykold White Line Paint coverage is approximately 3.9-5.2 kg (0.75-1 gallon) of line paint per standard size tennis court.

5.0 Installation Guidelines

5.1 Surface Preparation

Wait approximately 24 hours after applying colour coatings before applying White Line Paint. For indoor installations, wait until colour coating materials are thoroughly cured.

Mix Laykold white Line Paint completely before applying. Do NOT add water. Tape and measured lines should be in accordance with the respective sporting organisations.

Using a high-quality roller, roll line paint for 1-2 coats, as specified. To improve crispness of the finished line, prime the tape prior to application of the line paint with the same finish colour coat material in which the surface has been coated.

6.0 Limitations

- Do not apply when surface temperature exceeds 54°C (130°F)
- Do not apply when temperatures are below 10°C (50°F) or when rain is imminent.
- Do not allow to freeze.
- Do not dilute.
- Drying time of 2-4 hours depending on weather conditions.

7.0 Technical Data

Viscosity	22,000-28,000	cPs
-----------	---------------	-----

Results based on temperature of 23°C (76°F) and 50% humidity

*Based on Standard formula calculation

Above figures are guide values and should not be used as a base for specifications. Please consult the Safety Data Sheet (SDS) for more details.



WHITE LINE PAINT

TECHNICAL DATA SHEET

8.0 Disclaimer

Advanced Polymer Technology Asia Pacific (APTA) believes the information herein to be true, accurate and reliable, however, recommendations or suggestions are made without guarantee. Since conditions and disposal are beyond our control, APTA disclaims any liability incurred in connection with the use of our products and information contained herein. No warranty, express or implied is given nor is freedom from any patent owned by APTA or others to be inferred.